

# FD Series Tunnel Dryer

## Fd Series Tunnel Dryer

- ? 25: 1 load ratio, one time drying two pressed linens (2 \* 75kg);
- ? The use of double vertical layout stainless steel heater, saving energy and the use of more reliable;
- ? Computer control system can be intelligent drying humidity inspection and control, flexible control drying process, improve work efficiency;
- ? With a front tilt function, the rapid realization of the material, the material automatically when the wind direction control system;
- ? Drums, filters are made of stainless steel;
- ? Transmission and fan are used frequency control;
- ? Access to double temperature control system;
- ? Optional steam, gas or heat conduction oil heating.

Item	Unit	FD150S	FD150G
Capacity	kg	150	150
Diameter	mm	1600	1600
Depth	mm	1570	1570
Motor	kw	4	4
Feeding (Width X Height)	mm	1100x735	1100x735
Out Tilt Angle	°	15	15
Feed Threshold Height	mm	1800	1800
Volume	m <sup>3</sup>	2.525	2.525
Fun Motor Power	kw	15	15
Dimension(Lxwxh)	mm	2930X2460X4240	2930X2460X4240
Gas heating	Enter The Heat	Kcal/h	284760
	Air Volume	m <sup>3</sup> /min	189
	Connection Size		1¼"
	Weight	kg	1932
steam heating	Enter The Steam(35bhp)	kg/h	510
	Air Volum	m <sup>3</sup> /min	249.2
	Steam Presure	bar	8
	Connection Size		2"
	Weight	kg	2154

Note: The above specifications are subject to change without notice.

Product link : <https://www.hoop86.com/?p=1130>