
Automatic Washer Extractor

Automatic Washer Extractor

- ? The use of advanced finite element optimization design framework structure, strong, stable;
- ? Windows CE operating system, the industry's first full-color touch screen, the operation easier;
- ? 350G high dewatering elution machine, greatly reducing the drying energy consumption, time;
- ? Patented door seal structure, easy and easy to open the door and the cloth is not caught.

Model	Unit	GLX-50	GLX-70	GLX-100	GLX-125
Capacity	kg	50	70	100	125
Washing speed	r/min	32	32	32	32
High spin speed	r/min	765	720	700	700
Dehydration	G	350	350	350	350
Water pressure	Mpa	0.25-0.6	0.25-0.6	0.25-0.6	0.25-0.6
Water consumption	L/ time	575	800	1250	1575
Compressed air pressure	Mpa	0.4-0.7	0.4-0.7	0.4-0.7	0.4-0.7
Compressed air consumption	L/ time	10	10	10	10
Steam pressure	Mpa	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6
Steam consumption	kg/h	30	45	68	83
Motor power	kW	5.5	7.5	11	18.5
Motor power	kg	2332	2623	4000	4400

Note: The above specifications are subject to change without notice.

Product link : <https://www.hoop86.com/?p=1143>