
SXT-F Tilting Washing Machine

Tilting Washing Machine

? Greater than 320G high dewatering rate of elution, to reduce the labor intensity and save time, reduce energy consumption;

? The introduction of foreign advanced and advanced airbag shock absorber technology, the vibration to reduce the minimum reduction, the machine stable operation, greatly extending the life of the machine.

Using a single exhaust airbag double dump structure, with a rod-type tilt limit mechanism to ensure that the machine before and after tilt accurate;

? Before and after the safety lock hook to ensure that the machine tilted when the rotation of the fulcrum stability;

? Double-channel insurance activities of the pin to ensure that the machine safe tilt.

Unique cage structure, no out of dead ends, providing a discharge efficiency;

User-friendly touch-screen computer controller, improve the manual, automatic and semi-automatic control of three ways

Model	Unit	XGQ-150TT
Capacity	kg	150kg
Drum size	mm	1300*1170mm
Speed (washing / high spin)	rpm	25/650rpm
motor power	kw	22kw
Inverter power	kw	22kw
Steam consumption ratio	kg	0.9kg/kg
Water pipe		DN50
Steam pipe		DN25
Dimension	mm	2100*2600*2200mm
Weight	kg	5300kg

Note: The above specifications are subject to change without notice.

Product link : <https://www.hoop86.com/?p=1165>