

New Ironing Machine

New Ironing Machine

- ? 300 ° perimeter, more energy efficient;
- ? Integral transmission structure is simple, reduce the point of failure;
- ? Screed with self-weight plus spring automatically tighten, the belt is always consistent with the elastic, so as to ensure the quality of ironing;
- ? Float ballast drainage flow, no pressure on the steam pressure to ensure that the normal.

Model	Unit	YZII-3000	YZIII-3000	YZIV-3000	YZIII-3300	YZIV-3300
Drum Diameter	mm	Ø800	Ø800	Ø800	Ø800	Ø800
Max Ironing Width	mm	3000	3000	3000	3300	3300
Ironing Speed	m/mm	3-15	3-20	3-25	3-20	3-25
Ironing temperature	℃	158	158	158	158	158
Steam Presure	MPa	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6
Steam Consumption	kg/h	180	260	340	300	350
Motor Power	kW	2.2	2.2	2.2	2.2	2.2
Power Supply	v	380V/50HZ/3P	380V/50HZ/3P	380V/50HZ/3P	380V/50HZ/3P	380V/50HZ/3P
L	mm	4160	4160	4160	4460	4460
W	mm	2280	3200	4500	3200	4500
H	mm	1420	1420	1420	1420	1420
Weight	kg	3200	4000	5200	4100	5300

Note: The above specifications are subject to change without notice.

Product link : <https://www.hoop86.com/?p=1242>